

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



infantry ②
J96 ②

④
X


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A45D 34/04, B65D 75/00, A61K 7/32		A1	(11) International Publication Number: WO 00/49908
			(43) International Publication Date: 31 August 2000 (31.08.00)
(21) International Application Number: PCT/EP00/01032			(74) Agents: PEARCE, Timothy et al.; Unilever PLC, Patent Department, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB).
(22) International Filing Date: 7 February 2000 (07.02.00)			
(30) Priority Data: 9904037.0 22 February 1999 (22.02.99) GB			
(71) Applicant (for AE AU BB CA CY GB GD GH GM IE IL KE LC LK LS MN MW NZ SD SG SL SZ TT TZ UG ZA ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB).			
(71) Applicant (for all designated States except AE AU BB CA CY GB GD GH GM IE IL IN KE LC LK LS MN MW NZ SD SG SL SZ TT TZ UG US ZA ZW): UNILEVER NV [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).			
(71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Maharashtra, 400 020 Mumbai (IN).			
(72) Inventor; and			Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.
(75) Inventor/Applicant (for US only): GARCIA, Jorge, Gonzales [MX/MX]; Ponds de Mexico, Cuernavaca Plant, Calle 21-E No. 1, Civac Jiutepec Morelos, Mexico, 62500 (MX).			

(54) Title: PACKAGE FOR A FLUID COSMETIC COMPOSITION

(57) Abstract

A package suitable for topically applying to human skin a fluid cosmetic composition, and particularly a fluid antiperspirant or deodorant composition which comprises a container having: a sidewall (1, 2) made from one or more impervious sheets which exhibit longitudinal rigidity and transverse flexibility and which are sealed longitudinally (3, 4) to enclose a volume, a flexible closure (5) for the bottom aperture sealed (6, 7) to the sidewall (1, 2), a closure (9) for the top aperture comprising a retaining seating (14) in which a roll ball (13) is mounted and a cap (17).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CJ	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

Package for a Fluid Cosmetic Composition

The present invention relates to a package for a fluid
5 cosmetic composition and more particularly to a package
suitable for dispensing a flowable antiperspirant or
deodorant composition.

Background

10

Flowable antiperspirant or deodorant compositions can
comprise a number of forms, such as a liquid or a cream, or
possibly a gel or micronized powder. Such flowable
compositions have been dispensed in a variety of packages.
15 One common package comprises a roll-on which comprises a
reasonably rigid tubular container having at one end a flat
base enabling it to stand upright and an opposed second end
having a mouth that acts as a seating for a ball which is
able to rotate within the seating and extends above the
20 seating, allowing it to dispense the composition topically.
A more recent development has been the employment of a ball
of larger diameter. The seating desirably has a
sufficiently flexible lip to permit the ball to be inserted
by being pressed into position. The ball is covered by a
25 cap, which can itself have a flat top surface that enables
the package to stand in an invert position. A roll-on
usually dispenses a liquid composition, which in many
instances is thickened to a sufficient extent to control its
egress under gravity through the aperture defined by the
30 ball and the inner surface of the mouth of the container.

The tubular container is commonly either a glass bottle or
formed by moulding a thermoplastic. Whilst such containers
have proven to be effective, glass containers can be heavy

- 2 -

and moulded thermoplastic containers need dedicated moulding equipment. Consequently, there is a continuing need to devise alternative forms of packaging.

5 Summary of the invention

According to the present invention, there is provided a package for topically applying a fluid cosmetic composition to human skin which comprises

- 10 (i) a container having
- (a) a sidewall made from one or more impervious sheets, each sheet having opposite longitudinally extending first and second edges, a first strip adjacent the first edge and a second strip
15 adjacent to the second edge, which sheets are flexible in a transverse direction, the first strip of one sheet being sealed to the second strip of the same sheet or to the second strip of a contiguous sheet when there are two or more
20 sheets forming a closed chain, thereby enclosing a longitudinally extending volume
 - (b) a first end which defines a non-linear aperture closed by an end sheet and
 - (c) a second end opposite to the first end which
25 defines a second non-linear aperture,
- (ii) a closure for the second end which includes a seating for a roll-ball,
- (iii) a roll-ball which is seated within the seating and is partially proud of the seating and
- 30 (iv) a cover for the roll-ball.

- 3 -

Advantageously, the package of the present invention provides an elegant means of forming a container for a fluid cosmetic composition, and particularly one which can be employed in conjunction with existing roll-ball applicators, i.e. seating plus ball plus cap. The choice of a transversely flexible material to make the sidewall enables it to conform easily to the seating for the roll ball. Moreover, as the composition flows out of the container, the sidewall deforms, until eventually the container is empty and the sidewall is flat. This deformation has two advantages. First, it becomes readily apparent when the container is almost empty, providing a timely warning to the user that further composition needs to be purchased. Secondly, the container empties without a corresponding ingress of air. This avoids or at least minimises any oxidation of the composition which air might cause.

Detailed Description of the Invention

In the present invention, the container is formed from either one flexible sheet which is bent around and sealed longitudinally or preferably a plurality of sheets which are joined longitudinally to form a chain which is bent round and sealed to enclose a volume. Especially preferably, two sheets are employed. The sheet or chain of sheets forming the sidewall is sufficiently flexible in the transverse direction to be bent around without cracking. Desirably, the sidewall exhibits sufficient rigidity longitudinally such that the container can stand upright, resting on the bottom edge of the sheet or sheets. The thickness of the sheet is desirably selected in order to combine appropriate

- 4 -

longitudinal rigidity with sufficient transverse flexibility. The sheet thickness is often selected within the range of from 0.02 to 1 mm, the thickness selected often taking into account the sheet material employed to make the
5 sidewall. The contents of the container may assist in providing longitudinal rigidity to the container.

The sidewall sheets are preferably formed from a thermoplastic material, such as polyethylene or
10 polypropylene and extruded sheets are especially suitable. Low density (LDPE) and ultra-low density (LLDPE) polyethylene sheets are particularly suitable, and most preferably co-extruded LDPE and LLDPE sheets are employed. The sheets can further comprise reverse printed polyester.

15 Particularly preferably, the longitudinal join between either the first and second strips or between the respective strips on contiguous sheets forms an external tab, that is to say that the inner face of one sheet is joined to itself
20 or to the inner face of a contiguous sheet. This represents a particularly convenient and relatively simple means to seal one sheet to another. The seal can be effected by adhesive for the sheet material disposed continuously along the strips adjacent to the sheet edge. Particularly
25 suitably, where the sheets are made from a thermoplastic or have a thermoplastic face that is to be joined, the sheets can be joined by heat welding.

The sidewall is preferably made from two side sheets. The
30 two side sheets can be placed the one upon the other and aligned, and joined whilst the sheets are flat, if desired.

- 5 -

Thereafter, the sidewall can be bent to enclose a suitable volume, for example by pushing the tabs towards each other. Preferably, the two sheets are each rectangular and sealed together along the longer edges, most preferably to the bottom edge. The ratio of the length to breadth of the sheet is preferably from 2:1 to 5:1 and especially from 3:1 to 4:1. The bottom edges of the sheets are not sealed together, but by virtue of being straight, enable the container to stand upright reasonably stably on its base after it has been filled.

The container preferably is dimensioned to contain from 20 to 100 mls cosmetic composition, such as antiperspirant or deodorant composition, and especially from 40 to 70 mls.

15

The first end of the container is closed by an end sheet, which is impervious to the fluid cosmetic composition. The sheet is preferably flexible, and highly desirably is formed from a thermoplastic material such as those contemplated for the sidewall. Desirably, the end sheet is disposed within the first end such that a strip on the end sheet adjacent to its circumferential edge and on its inner face is in contact with the inner face of the sidewall, adjacent to the bottom edge of the sidewall. The end sheet can be sealed to the sidewall by adhesive or hot welding. The end sheet advantageously is a planar sheet which is bent and positioned such that in the container it is non-planar, and particularly is convex in profile, normally extending downwardly in longitudinal cross section from edge to middle of the side sheets. This can be achieved by the end sheet advantageously being sealed to the side sheets closer to the

- 6 -

second end at the side-edge of the side sheets and progressively further from the second end approaching the middle of the side sheets, normally symmetrically.

- 5 The sidewall, preferably formed from two side sheets, and first end of the container desirably form a pouch made from two sheets forming the sidewall and an end sheet, each made of a thermoplastics material, sealed together by hot welding contiguous faces adjacent to their edges. When the
10 container has been filled, the pouch at or adjacent to its base (first end) in transverse cross section usually has a maximum front to back spacing between the side sheets relative to the width of the pouch, of from 4:3 to 3:1 and particularly about 2:1, normally tapering to an acute
15 nterfacial angle at the longitudinal seal of the side sheets.

- The second end of the container comprises a non-linear aperture which is closed by the applicator seating. The
20 seating suitably comprises a topwall, which preferably is oval, a skirt surrounding the topwall and depending from it, a circular aperture centrally located in the topwall, an upstanding collar surrounding the circular aperture and having inwardly projecting seating means that are
25 dimensioned and spaced longitudinally so as to retain a suitably dimensioned rotatable ball. The topwall and skirt together normally form a rigid closure.

- The skirt is dimensioned to fit closely within the non-
30 linear aperture of the container and is preferably sealed to the sidewall closely adjacent to the top edge of the

- 7 -

sidewall. The skirt can further comprise a pair of downwardly pointing strengthening lugs located in the vicinity of the roll ball, i.e. below the collar, preferably symmetrically disposed. Preferably there are two such lugs.

5 The sealing can be accomplished by adhesive or more preferably by heat welding or by ultrasonic welding.

The collar may comprise a single unit housing the ball seating means or it may alternatively comprise a base to
10 which is attached a seating unit for the ball, for example by a screw connection or by a tight push fitting. The seating means conveniently comprises an upper and a lower lip, each preferably presenting a concave profile to the ball. As is conventional in roll ball applicators, the
15 spacing between the ball and the inner wall of the collar is most desirably dimensioned to permit the ball to rotate and carry a film of cosmetic composition from within the package to an exposed area of ball that can be contacted topically to human skin, whilst preventing the ball from falling out
20 of the seating or being pushed into the container on topical application of the cosmetic fluid to human skin. The collar can be provided with an external screw thread to engage with a correspondingly threaded cap for the collar, or the cap can push fit onto the collar.

25

The seating and the cap are each desirably moulded thermoplastic, for example polyethylene or polypropylene and especially a high density polyethylene.

30 The diameter of the unit housing the ball is at the discretion of the package manufacturer. Preferably the

- 8 -

housing has an internal diameter that is suitable to house a ball having a diameter selected in the range of from 20 to 50 mm. Particularly convenient ball diameters are either 25 or 35 mm.

5

The ball is often a hollow moulded thermoplastic ball, though alternative materials can be employed if desired.

10

The invention also provides a product comprising a package according to the first aspect described hereinbefore, in which the container contains a fluid antiperspirant or deodorant composition that can flow or be squeezed through the aperture by application of normal hand pressure to a flexible side-walled container. Such a formulation is normally observable as a thickened liquid or a cream, and usually has a viscosity within the range of from 500 to 100000 mPas.s.

15

Viscosity measurements herein correspond to those made using a Brookfield TM RVT viscometer, No 2 spindle, at 20 rpm at 25°C.

20

The compositions normally comprise one or more of a) an antiperspirant active and/or b) a deodorant active, a) normally being selected in the range of 0.5 to 60%, often from 5 to 40% and b) normally being selected in the range of from 0.1 to 90% and often up to 60%. The antiperspirant active a) is often an astringent aluminium zirconium or mixed aluminium zirconium salt or a complex thereof, such an aluminium chlorohydrate or a zirconium aluminium complex or an activated chlorohydrate or complex. The deodorant active

25

30

- 9 -

can comprise a monohydric C1-C4 alcohol such as ethanol or isopropanol, in which case it is often present at a concentration of at least 10% especially at least 20%, and can function at least in part as a carrier as well as
5 deodorant. The deodorant can additionally or alternatively comprise bactericides such as chlorinated aromatics or biguanides, often at a concentration of not more than 5% and particularly up to 2%.

10 Formulations employed herein commonly comprise from 10 to 95% of a carrier and especially from 30 to 90%. The carrier can comprise a single phase, be it hydrophobic or hydrophilic, or can comprise a mixture of such phases, normally present as an emulsion. Suitable hydrophobic
15 carriers can include volatile silicone oils such as cyclomethicones (especially tertramer, pentamer and/or hexamer) or corresponding volatile linear methicones, and/or non-volatile hydrocarbon oils. Other suitable carriers include aliphatic ethers or esters containing a C8 to C30
20 group.

Hydrophilic carriers include water, aliphatic monohydric alcohols, especially ethanol, glycols or tri or polyhydric alcohols.

25

The increase in viscosity of the fluid formulation is normally obtained by incorporation of one or more structurants, gellants or thickeners in an amount selected from 0.1 to 10% particularly from 0.2 to 5% and in many
30 embodiments from 0.3 to 2% to increase the viscosity to the formulation to within the desired range for a cream.

- 10 -

Suitable structurants include synthetic or natural carbon-based waxes, e.g. beeswax, hydroxystearic acid or castor wax or silicone waxes, or silicone elastomers. Suitable gellants include fatty alcohols, certain amide derivatives of tricarboxylic acids, dibenzylidene sorbitol and N-acyl amino acid derivatives, e.g. n-lauroyl-L-glutamic acid dibutylamide. Suitable thickeners can include gums, starches cellulose derivatives and inorganic thickeners such as clays or silica. Some viscosity increase can also be achieved by selection of carrier constituents of higher viscosity or by incorporation of particulate actives.

The formulation can also contain one or more conventional minor additives, such as in an amount of up to 10%, such as fragrance, talc, or humectant (glycerol or sorbitol).

Except in operative or comparative examples, all numbers herein indicating amounts or ratios of materials, such as limits of ranges are to be understood as modified by about, unless expressly stated otherwise.

In operation, the container is grasped in one hand and either it is inverted or/and pressure is applied to opposing facets of the sidewall, thereby ensuring that the fluid formulation makes contact with the ball and be carried out of the container as a surface layer on the ball as it rotates as a result of being rolled across the skin. Hence, the formulation is distributed over the surface of the skin.

- 11 -

A package according to the present invention will now be described more fully by way of example only and with reference to the accompanying Figures in which:-

- 5 Figure 1 represents a side view of the package with cap removed;
- Figure 2 represents a view of the base and side of the package with cap in place;
- Figure 3 represent a top view of the package with cap
- 10 removed;
- Figure 4 represents a sideways longitudinal cross-section through the package with cap removed;
- Figure 5 represents an endways longitudinal cross section through the package with cap removed.
- 15
- In the Figures, the package comprises a container formed from a front flexible sheet 1 and a rear flexible sheet 2 which are heat welded together along two longitudinally extending strips 3 and 4 adjacent to their longitudinal
- 20 edges, and a flexible bottom sheet 5 which is heat welded to respectively front sheet 1 along bottom strip 7 and to front sheet 2 along bottom strip 6, strips 6 and 7 being deeper where they are sealed to strips 3 and 4 than where they are remote from strips 3 and 4. The flexible sheets 1 and 2 are
- 25 made from co-extruded low density polyethylene and ultralow density polyethylene and exhibit flexibility in a transverse direction, whilst retaining stiffness longitudinally. The bottom edge 8 of each of the sheets 1 and 2 is orthogonal to their longitudinally extending edges, so that the container
- 30 can rest on the bottom edge 8 and stand upright. The flexible bottom sheet 5 is downwardly extending arcuate in

- 12 -

cross section. The upper end of the container is closed by a moulded closure which comprises an oval top surface 9 from which depends a skirt 10 which is heat sealed to flexible sheets 1 and 2. The skirt 10 has a pair of tabs 11 and 12.

- 5 Located centrally within the top surface 9 of the closure and a seating for a roll ball 13 which comprises an upstanding circular collar 14 provided with an concave upper lip 15 and a concave lower lip 16 which together act as a seating for the roll ball 13, permitting it to rotate but
10 preventing it from falling out and falling into the container. The upstanding circular collar 14 has an external threading which co-operates with 176 to cover the roll ball 13 when the package is not in use.

15 Examples 1 to 9

These Examples describe fluid formulations which are suitable for employment in a package according to Figures 1 to 5.

- 13 -

The Table

Constituent	Per cent by weight								
Example No	1	2	3	4	5	6	7	8	9
Ethanol		30		60				30	
Isopropanol	30		30		30	60	30		
Hydroxypropyl-cellulose	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	
ACH		4	4				20		
AZH								20	
AZAG									20
PHMB				0.2	0.2				
Triclosan						0.1			
Suspending Agent									3
Propylene Carbonate									1
Talc									6
Water + minors	To 100	to 100	to 100	to 100	to 100	to 100	to 100	to 100	
Cyclomethicone + minors									to 100

ACH represents aluminium chlorohydrate, AZH represents aluminium zirconium pentachlorohydrate, AZAG represents aluminium zirconium tetrachlorohydrate glycine complex, and PHMB represents poly(hexamethylenebiguanide).

- 14 -

Claims:

1. A package for topically applying a fluid cosmetic composition to human skin which comprises
 - 5 (i) a container having
 - (a) a sidewall made from one or more impervious sheets, each sheet having opposite longitudinally extending first and second edges, a first strip adjacent the first edge and a second strip
10 adjacent to the second edge, which sheets are flexible in a transverse direction, the first strip of one sheet being sealed to the second strip of the same sheet or to the second strip of a contiguous sheet when there are two or more
15 sheets forming a closed chain of sheets, thereby enclosing a longitudinally extending volume
 - (b) a first end which defines a non-linear aperture closed by an end sheet and
 - (c) a second end opposite to the first end which
20 defines a second non-linear aperture,
 - (ii) a closure for the second end which includes a seating for a roll-ball,
 - (iii) a roll-ball which is seated within the seating and is partially proud of the seating and
25 (iv) a cover for the roll-ball.
2. A package according to claim 1 in which the sheet having an inner face in contact with the enclosed volume and first and second longitudinally extending
30 edges is bent around such that the inner face adjacent to the first longitudinally extending edge is sealed to

- 15 -

the inner face of the sheet adjacent to the second longitudinally extending edge.

3. A package according to claim 1 or 2 in which the side-wall comprises a pair of flexible sheets which are joined by two longitudinally extending fluid-tight seals and are bent around to enclose a longitudinally extending volume.
4. A package according to any preceding claim in which the flexible sidewall sheets are joined by heat welding.
5. A package according to any preceding claim in which the flexible sidewall sheets comprise co-extruded low density polyethylene and ultra-low density polyethylene.
6. A package according to any preceding claim in which the flexible bottom sheet has a downwardly extending convex profile.
7. A package according to any preceding claim in which the closure for the second end comprises a topwall, preferably oval, a skirt surrounding the topwall and depending therefrom, a circular aperture located centrally within the topwall, an upstanding collar surrounding the circular aperture and having inwardly projecting seating means that are dimensioned and spaced longitudinally so as to retain rotatably a suitably dimensioned ball.

- 16 -

8. A package according to claim 7 in which the skirt has downward lugs positioned below the collar.

5 9. A package according to any preceding claim in which the closure is heat sealed to the sidewall.

10. A product comprising a package according to any preceding claim in which the container contains a flowable antiperspirant or deodorant composition.

10

Fig.1.




Fig.2.




Fig.3.




Fig.4.





Fig.5.



INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 00/01032

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A45D34/04 B65D75/00 A61K7/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A45D B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 30 00 784 A (METAL BOX LTD.) 24 July 1980 (1980-07-24) page 6, paragraph 3; claim 1; figures 1,2 page 7, last paragraph -page 8, paragraph 4	1-4, 6, 7, 9
Y	DE 89 00 884 U (INDAG GESELLSCHAFT FÜR INDUSTRIEBEDARF MBH) 23 March 1989 (1989-03-23) page 1, paragraph 3 -page 3, paragraph 1; figures 1,3,5	1-4, 6, 7, 9
A		5, 10
A	FR 2 630 409 A (A. TARTAGLIONE) 27 October 1989 (1989-10-27) page 1, line 7 - line 34; figures 1,2	1, 10
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

7 June 2000

Date of mailing of the international search report

20/06/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5618 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Schmitt, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/01032

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 257 865 A (KANARI TANI) 2 November 1993 (1993-11-02) column 1, line 10 - line 15; figures 2,3	1-4,6,7, 10
A	FR 1 263 715 A (VITHERM) 11 October 1961 (1961-10-11) page 1, left-hand column, paragraph 1 - paragraph 2; figures 4,5	1
A	EP 0 515 745 A (STANDIPACK PRIVATE LTD) 2 December 1992 (1992-12-02) abstract; figure 1	5
A	US 4 732 299 A (E.E. HOYT) 22 March 1988 (1988-03-22) column 3, line 10 - line 34; figures 2,3	8

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 00/01032

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 3000784 A	24-07-1980	GB 2044683 A DE 8000536 U	22-10-1980 15-11-1984
DE 8900884 U	23-03-1989	AT 87875 T CA 2045555 A DE 59001144 D DK 380107 T WO 9008703 A EP 0380107 A EP 0455732 A JP 4503045 T NO 912913 A	15-04-1993 27-07-1990 13-05-1993 17-05-1993 09-08-1990 01-08-1990 13-11-1991 04-06-1992 25-07-1991
FR 2630409 A	27-10-1989	NONE	
US 5257865 A	02-11-1993	JP 5201455 A	10-08-1993
FR 1263715 A	11-10-1961	NONE	
EP 0515745 A	02-12-1992	AT 128430 T DE 69113449 D DE 69113449 T ES 2080253 T	15-10-1995 02-11-1995 07-03-1996 01-02-1996
US 4732299 A	22-03-1988	NONE	

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)